

SCREW TERMINAL TYPE ALUMINUM ELECTROLYTIC CAPACITORS

New


FXW Series

Useful of 8,000 hours at 85°C (Warranty of 5,000 hours at 85°C)

• Conform RoHS

Features

- Capacitance has been increased by 35% compared with FX2 model by special etched foil technology and new structure of element.
- High reliability series with the warranty of 5,000 hours realized through improvement of the HCGWA type into a longer-life type.



(unit : mm)

φ D	P	S	T	Cap material
77	32.0	M5×10	5.0	Phenol
90	32.0	M5×10	5.0	Phenol
101	32.0	M6×12	3.0	PPS


Product Specifications

Items	Specifications
Temperature range	-10°C ~ +85°C
Rated voltage	350 ~ 450V.DC
Capacitance tolerance	±20% (20°C, 120Hz)
Leakage current	0.01CV (μA) or 7mA, whichever is smaller or less [C = nominal capacitance (μF), V = rated voltage (V)]
Dissipation factor	Less than the value specified in the standard products table. (20°C, 120Hz)
Permissible ripple current	As specified in the standard products table. (40°C, 120Hz)
High-temperature load	After the rated voltage with specified ripple current is applied at 85°C for 5000 hours: Capacitance tolerance: ±15% or less of the initial value Dissipation factor: 175% or less of the specified initial value Leakage current: Specified initial value or less
Others	JIS C 5101-4.

Ripple current correction coefficient

Temperature (°C)	40	60	70	85
Correction coefficient	1.0	0.75	0.62	0.37
Frequency (Hz)	120	300	1k	≥10K
Correction coefficient	1.0	1.1	1.3	1.4

* When using this capacitor at a frequency below 120Hz, contact us in advance.



Bracket

- See page 51 for shapes and dimensions.
- Product names in the Standard Products Table correspond to the bracket for Type Y, but Type I bracket may be used (Type of bracket code = I).
- If bracket are not necessary, enter "N" for the type of bracket code.
- Bracket will be delivered separately.

Standard Products Table

Rated Voltage Code (Surge Voltage) (V. DC)	Capacitance (μF)	Case size φDXL(mm)	tanδ 20°C, 120Hz	Ripple current 40°C, 120Hz (Arms)	ESR(typ.) 20°C, 100Hz (mΩ)	Z max 20°C, 10kHz (mΩ)	ESL(typ.) (nH)	Product name
350 2V (400)	13000	77×155	0.70	20.7	25	26	26	FXW2V133YE155PH
	17000	77×195	0.70	25.4	19	20	26	FXW2V173YE195PH
		90×157	0.70	25.4	19	20	26	FXW2V173YF157PH
	22000	77×235	0.70	32.1	17	18	26	FXW2V223YE235PH
		90×196	0.70	33.8	16	18	26	FXW2V243YF196PH
	24000	101×175	0.70	33.8	16	18	36	FXW2V243YG175
		90×236	0.70	39.7	12	13	26	FXW2V303YF236PH
30000	101×195	0.70	39.7	12	13	36	FXW2V303YG195	
	101×237	0.70	45.6	10	12	36	FXW2V383YG237	
400 2G (450)	11000	77×155	0.70	19.2	31	32	26	FXW2G1133YE155PH
	13000	77×195	0.70	23.0	26	27	26	FXW2G133YE195PH
		90×157	0.70	24.0	23	24	26	FXW2G153YF157PH
	16000	77×235	0.70	28.0	21	22	26	FXW2G163YE235PH
		90×196	0.70	30.0	21	22	26	FXW2G193YF196PH
	20000	101×175	0.70	29.4	20	21	36	FXW2G203YG175
		90×236	0.70	35.9	17	18	26	FXW2G243YF236PH
	24000	101×195	0.70	33.8	17	18	36	FXW2G243YG195
101×237		0.70	40.5	13	14	36	FXW2G303YG237	

SCREW TERMINAL TYPE ALUMINUM ELECTROLYTIC CAPACITORS

Rated Voltage Code (Surge Voltage) (V _{DC})	Capacitance (μF)	Case size øDXL(mm)	tanδ 20°C, 120Hz	Ripple current 40°C, 120Hz (Arms)	ESR(typ.) 20°C, 100Hz (mΩ)	Z _{max} 20°C, 10kHz (mΩ)	ESL(typ.) (nH)	Product name
450 2W (500)	9000	77×155	0.70	17.4	38	39	26	FXW2W902YE155PH
	11000	77×195	0.70	21.2	31	32	26	FXW2W113YE195PH
	12000	90×157	0.70	20.2	28	29	26	FXW2W123YF157PH
	14000	77×235	0.70	26.4	25	27	26	FXW2W143YE235PH
	16000	90×196	0.70	27.1	23	25	26	FXW2W163YF196PH
	17000	101×175	0.70	27.1	21	22	36	FXW2W173YG175
	20000	90×236	0.70	32.7	19	20	26	FXW2W203YF236PH
		101×195	0.70	30.7	19	20	36	FXW2W203YG195
25000	101×237	0.70	37.0	17	18	36	FXW2W253YG237	

Life time graph

Useful life depending on ambient temperature T_a and ripple current operating conditions I_r versus rated ripple current at 40°C, 120Hz

