

BASICS OF CAPACITORS

*When placing an order:

When placing an order, please order a quantity equal to an integral multiple of the basic ordering unit of a specific product.

Aluminum electrolytic capacitor

Snap mount type

| φ D (mm) | Q'ty |
|----------|------|
| φ 20 | 100 |
| φ 22 | 100 |
| φ 25 | 100 |
| φ 30 | 100 |
| φ 35 | 100 |
| φ 40(41) | 80 |
| φ 46 | 80 |
| φ 51 | 80 |

Screw terminal type

| φ D (mm) | Q'ty |
|----------|------|
| ø36 | 100 |
| ø51 | 50 |
| ø64 | 50 |
| ø77 | 50 |
| ø90 | 50 |
| ø101 | 50 |
| ø121 | 20 |

Radial type

| Series | Q'ty |
|--------|------|
| HU | 300 |
| SR | 1000 |

Film capacitor

For SMD capacitors, taped

| Series | Rating | Package quantity / reel |
|--------|--------|-------------------------|
| MMX-EC | 100V | 0.01 ~ 0.12μF |
| | | 0.15 ~ 0.22μF |
| MML-E | 100V | 0.01 ~ 0.22μF |
| | 250V | 0.01 ~ 0.1μF |
| MML-F | 100V | 0.47 ~ 1.0μF |
| | 160V | 1.0μF |
| | 630V | 0.01 ~ 0.033μF |

Resin dip type capacitors, taped (Ammo Pack)

| Series | Rating | Package quantity/box |
|--------|-----------------|----------------------|
| MDDSA | 100V | 0.01 ~ 0.22μF |
| | | 0.27 ~ 0.33μF |
| | | 0.39 ~ 0.47μF |
| | | 0.56 ~ 0.68μF |
| | | 0.82 ~ 1.0μF |
| | | 1.2 ~ 2.7μF |
| | | 3.3μF |
| | | 0.01 ~ 0.082μF |
| | | 0.1 ~ 0.12μF |
| | | 0.15μF |
| | 250V | 0.18 ~ 0.22μF |
| | | 0.27 ~ 0.33μF |
| | | 0.39 ~ 1.2μF |
| | | 0.01 ~ 0.027μF |
| | | 0.033μF |
| | | 0.039 ~ 0.047μF |
| | 400V | 0.056 ~ 0.1μF |
| | | 0.12 ~ 0.47μF |
| | | 0.01 ~ 0.012μF |
| | | 0.015 ~ 0.027μF |
| 630V | 0.033 ~ 0.047μF | |
| | 0.056 ~ 0.15μF | |
| | 0.01 ~ 0.012μF | |
| | 0.015 ~ 0.027μF | |

Bulk products

| Series | Q'ty |
|-------------|------|
| MDDSA | 1000 |
| MDD(5) | |
| MDD-HD(5Y) | |
| MDD-HD(4H) | |
| MDD-HD(4) | |
| MDD-HD(4HS) | |
| MDD-P(4) | |
| MKC-JS | |

| Series | Q'ty |
|--------|------|
| MDD-HF | 500 |
| MDD-P | |
| MTB-P | |
| MTBS | |
| MTB | |
| WMTB | 100 |
| WMTB-P | |