

# TANTALUM ELECTROLYTIC CAPACITORS


## TMCS Series (Standard Tantalum Chip Capacitors)

### Features


- The product is a standard type that has been most widely used among tantalum chip capacitors. The product has high solder heat resistance and is suitable for automatic mounting.
- The product is provided with both excellent frequency characteristic and excellent impedance characteristics.

Product symbol : (Example) TMCS Series A case 16V 1μF ±20%

**TMCS A 1C 105 M T R F**



### Outline of drawings and dimensions



### Dimensions

(Unit: mm)

Case code	Case size				
	L <sup>+0.2</sup>	W <sup>+0.2</sup>	H <sup>+0.2</sup>	l <sup>+0.3</sup>	a <sup>+0.2</sup>
A	3.2	1.6	1.6	0.7	1.2
B	3.5	2.8	1.9	0.8	2.2
C	5.8	3.2	2.5	1.3	2.2
E	7.3	4.3 <sup>+0.3</sup>	2.8	1.3	2.4

### Standard value and case size

Capitance		Rated voltage (V.DC)						
μF	Code	4	7	10	16	20	25	35
		0G	0J	1A	1C	1D	1E	1V
0.10	104							A
0.15	154							A
0.22	224							A
0.33	334							A
0.47	474						A	B
0.68	684					A		B
1.0	105				A			B
1.5	155			A			B	C
2.2	225		A			B		C
3.3	335	A			B			C
4.7	475			B			C	E
6.8	685		B			C		E
10	106	B			C		E	
15	156			C		E		
22	226		C		E			
33	336	C		E				
47	476		E					
68	686	E						

Product specifications	TMCS	Test conditions JIS C5101-1:1998																			
Operating temperature range	-55°C ~ +125°C																				
Rated voltage	DC4 ~ 35V	85°C																			
Surge voltage	DC5 ~ 45V	85°C																			
Derated voltage	DC2.5 ~ 22V	125°C																			
Capacitance	0.1 ~ 68μF																				
Capacitance tolerance	±10% or 20%	Paragraph 4.7, 120 Hz																			
Leakage current	0.01 CV or 0.5μA, whichever is larger or less	Paragraph 4.9, in 5 minutes after the rated voltage is applied.																			
tanδ	0.1 ~ 1.0    0.04 or less 1.5 ~ 68    0.06 or less	Paragraph 4.8, 120Hz																			
Surge withstanding voltage	ΔC/C ±5% or less tanδ Specified initial value or less LC Specified initial value or less	Paragraph 4.26																			
Temperature characteristics	<table border="1"> <thead> <tr> <th>Specified initial value</th> <th>-55</th> <th>85</th> <th>125</th> </tr> </thead> <tbody> <tr> <td>ΔC/C</td> <td>-</td> <td>-10 ~ 0%</td> <td>0 ~ +10%</td> <td>0 ~ +12%</td> </tr> <tr> <td>tanδ</td> <td>0.04</td> <td>0.04</td> <td>0.05</td> <td>0.05</td> </tr> <tr> <td>Leakage current</td> <td>0.06</td> <td>0.06</td> <td>0.07</td> <td>0.07</td> </tr> </tbody> </table> or less LC 0.01CV or 0.5μA or less    —    0.1CV or 5μA or less    0.125CV or 6.25μA or less	Specified initial value	-55	85	125	ΔC/C	-	-10 ~ 0%	0 ~ +10%	0 ~ +12%	tanδ	0.04	0.04	0.05	0.05	Leakage current	0.06	0.06	0.07	0.07	Paragraph 4.24
Specified initial value	-55	85	125																		
ΔC/C	-	-10 ~ 0%	0 ~ +10%	0 ~ +12%																	
tanδ	0.04	0.04	0.05	0.05																	
Leakage current	0.06	0.06	0.07	0.07																	
Solder heat resistance	ΔC/C ±5% or less tanδ Specified initial value or less LC Specified initial value or less	Solder Dip 260±5°C A,B case C,E case 10±1 sec. 5±0.5 sec. Reflow-260°C 10±1 sec.																			
Moisture resistance no load	ΔC/C ±5% or less tanδ Specified initial value or less LC Specified initial value or less	Paragraph 4.22, 40°C 90 ~ 95%RH,500hours																			
High-temperature load	ΔC/C ±10% or less tanδ Specified initial value or less LC 125% Specified initial value or less	Paragraph 4.23, 85°C The rated voltage is applied for 2000 hours.																			
Thermal shock	ΔC/C ±5% or less tanδ Specified initial value or less LC Specified initial value or less	Leave at -55°C, normal temperature, 125°C, and normal temperature for 30 min., 3 min., 30 min., and 3 min. Repeat this operation 20 times running.																			
Moisture resistance load	ΔC/C ±10% or less tanδ 150% Specified initial value or less LC 125% Specified initial value or less	40°C, humidity 90 to 95%RH The rated voltage is applied for 500 hours.																			
Failure rate	1%/1000hours	85°C. The rated voltage is applied (through a protective resistor of 1 Ω/V).																			

※ This catalog is designed for providing general information. Please inquire of our Sales Department to confirm specifications prior to use.

